

the following buildings: composed of (4)

- a. Proper headquarters and departmental offices
- b. Living quarters and recreational room for the troops being in service
- c. Transit barracks for troops and officers with large capacity
- d. Store-rooms
- e. Diverse maintenance and repair-shops
- f. Doctor's office and sick wards
- g. Machinery center (water pumps, sewage-disposal etc.)
- h. Guards-rooms
- i. Immediately adjoining the District seat buildings apartments for officers and nco's
- h. Diverse cellar (sub-ground level) rooms
- i. Stables

Each district was composed of the buildings mentioned above. District seat buildings constructed after '49 were practically identical even in detail, so this type of district seat can be well studied on the attached map-sketch on the District Headquarters of the Border Guard of the Ministry of Interior at Cooma.

(Buildings erected after '48 were built of ^{Bardipara} brick and steel reinforced concrete elements. The main walls were 3 ft cm thick made of small sized bricks, dividing walls were 12 cm thick and the roof-structure was ^{made of} prefabricated steel-reinforced concrete logs with brick bars (!))

(4)

Ezek az ujonnan epult Kerulet szekhelyek a kovetkezo epuletekbol tevodtek

ossze:

- a. Megkelelo parancsnoksagi es szakosztalyi irodahelysegek.
- b. lakó es szorakozo helysegek az itt szolgálatot teljesito le-
genysegnek.
- c. Nagy befogadokepessegu legenysegi es tiszti atvonalasi korle-
tek.
- d. Raktarhelysegek.
- e. Kulonbozo karbantarto es javito muhelyek.
- f. Orvosi rendelo es gyongelkodo szobak.
- g. Gephaszak. (vizszivattyuk, szemmyviseltavolito stb.)
- h. Orszobak.
- j. Kosvetlen a Kerulet szekhely mellett tiszti es tovabbszolgaló
tiszthelyettesi lakasok.
- k. Kulonbozo pincsehelysegek.
- l. Istallek.

Minden Keruletsszekhely a fent felsorolt epuletekbol tevodott esze.

Az 1949-ben es utan epített kerulet szekhelyek epuletei majdnem teljes
egeszukben megegyeztek egymassal, ezért a csatolt B.M. Hatarország Kerulet
Parancsnoksag Csorna terkepvaszlatan az ilyen tipusu kerulet szekhelyek
tamlmanyozhatek.

(Az 1948 utan epített Hatarorségi epuletek teglából es vasbeton elemek-
bol keszultek. 38 cm. vastag kismeretu teglából keszult szerkezeti fe-
falak, 12 cm. vastag valaszfalak es elegyartott vasbeton gerenda-teglatalcas
fedemek.)